

Product	Primary Port	Uplink	Temp Range	PoE Power	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)
CHASSIS-BASED SWITCHES — LAYER 3						
SwitchBlade® x8112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	80	155
SwitchBlade® x8106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	80	120
10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 3						
x930-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	48	48
x930-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	24	24
x510-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	12	24
x510-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	12	24
x510L-52GP	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	6	12
x510L-28GP	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	6	12
10/100/1000 MANAGED SWITCHES — LAYER 3						
IE300-12GP	8 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to 75°C	240W	8	8
10/100 MANAGED SWITCHES — STACKABLE LAYER 3						
x310-50FP	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	12	24
x310-26FP	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	12	24
CHASSIS-BASED SWITCHES — LAYER 2						
SwitchBlade® x3112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	80	155
SwitchBlade® x3106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	80	120
10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 2						
IX5-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	370W or 720W	24	24
GS948MPX	48 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	12	24
GS924MPX	24 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	12	24
10/100/1000 MANAGED SWITCHES — LAYER 2						
x230-28GP	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	12	24
x230-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	8	16
x230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	4	8
IE200-6GP	4 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	4
10/100 MANAGED SWITCHES — STACKABLE LAYER 2						
FS980M/52PS*1	48 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	12	24
FS980M/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	12	24
10/100 MANAGED SWITCHES — LAYER 2						
FS980M/18PS*2	16 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	250W	8	16
FS980M/9PS*3	8 x Fast Ethernet	1 x Gigabit Ethernet	0°C to 50°C	150W	4	8
IE200-6FP	4 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	4
IFS802SP/POE(W)	8 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	123.2W	-	8

¹ Available end of Oct/2016

² Available in Nov/2016

³ Available in Q1/2017

Product	Primary Port	Uplink	Temp Range	PoE Power	Total no. of PoE+ enabled ports (30W)	Total no. of PoE enabled ports (15.4W)
10/100/1000 UNMANAGED AND WEBSMART SWITCHES						
GS950/48PS	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	370W	12	24
GS950/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	185W	4	12
GS950/16PS	14 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	6	12
GS950/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	75W	2	4
GS900/8PS	8 x Gigabit Ethernet	1 x Gigabit Ethernet	0°C to 40°C	75W	2	4
10/100 UNMANAGED AND WEBSMART SWITCHES						
FS750/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 40°C	193W	4	12
FS708LE/POE	8 x Fast Ethernet	-	0°C to 40°C	30W	-	2

NETWORK INTERFACE CARDS (PCIe)						
2716POE/FXSC	Fast Ethernet	MMF SC	0°C to 40°C	15W	-	1
2716POE/FXST	Fast Ethernet	MMF ST	0°C to 40°C	15W	-	1
2911GP/LXLC	Gigabit Ethernet	SMF LC	0°C to 40°C	30W	1	1
2911GP/LXSC	Gigabit Ethernet	SMF SC	0°C to 40°C	30W	1	1
2911GP/SFP	Gigabit Ethernet	SFP	0°C to 40°C	30W	1	1
2911GP/SXLC	Gigabit Ethernet	MMF LC	0°C to 40°C	30W	1	1
2911GP/SXSC	Gigabit Ethernet	MMF SC	0°C to 40°C	30W	1	1
MEDIA CONVERTERS						
PC232/POE	Fast Ethernet	100FX MMF	0°C to 40°C	15W	-	1
PC2002POE	Gigabit Ethernet	SFP	0°C to 40°C	15W	-	1
IMC1000TP/SFP	Gigabit Ethernet	SFP	0°C to 40°C	30W	1	1
INJECTOR/MIDSPAN						
6101GP	Gigabit Ethernet	Gigabit Ethernet	0°C to 40°C	30W	1	1
6112GP	12 x Gigabit Ethernet	12 x Gigabit Ethernet	0°C to 40°C	370W	12	12



IQ TRADING - ОФИЦИАЛЬНЫЙ ДИСТРИБЬЮТОР В УКРАИНЕ
 Украина, 04080, Киев, ул. Межигорская, 87-а, оф. 30
 тел.: +380 (44) 351-14-37, факс: +380 (44) 351-14-38
 e-mail: disti@iqtrading.com.ua, web: www.iqtrading.com.ua



NETWORK SMARTER

North America Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895
 Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830
 EMEA & CSA Operations | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

© 2016 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.
 C618-3410015 RevK